

MAIN APPLICATIONS

FIT LOCK is a revolutionary patented system that allows quick and easy positioning of panels both on ceilings and/or on walls. The concentric locking system of FIT LOCK allows the adjustment of the position once they are put in place.

FIT LOCK is easy to remove and to reposition, allowing the more complicated operations of inspection-maintenance or their replacement if needed.

The unit is a MUST in the boat market, for the positioning of ceiling panels and side panels and is largely used in the railway, automotive, motor home, exhibition and building markets.

TECHNICAL CHARACTERISTICS

MATERIAL : acetylic

FIRE RESISTANCE : self extinguishing COLOUR : self extinguishing white

COLOUR : white SIZE : 60 mm diameter

TRACTION FORCE : 22 Kg.

MATERIAL : nylon
FIRE RESISTANCE : //
COLOUR : grey

SIZE : 60 mm diameter

TRACTION FORCE : 11 Kg.

HOW TO USE

MANUAL POSITIONING: with the help of the positioning marker devices, the two components, that are part of the FIT LOCK, are installed on the elements to be connected

CAD-CAM POSITIONING: ideal for large surfaces, allows the reference positions of the FIT LOCK to be inserted even during the engineering phase.

Patent deposited at: European patent office in Monaco

All the information contained herewith is given in good faith but without guarantee, the user is anyhow compelled to verify the correctness of the characteristics of the product for their specific use. From this information no liberty of possible patents can be deducted.

ARREDOMARE s.r.l. Via del Tiglio, Loc. Sardina 56030 Calcinaia (PI) Tel. 0587 755931 Fax 0587 756180 info@fitlock.it – www.fitlock.it

