


# OKS 2521 - Product Information

### Fields of Application:

Repair of galvanising interrupted or damaged during welding, drilling or cutting (hot galvanising, electrogalvanising or flame-spray galvanising) without subsequent painting. Can be used for weathering-resistant corrosion protection in two-layer application.

## OKS 2521 Gloss Zinc, Spray



#### **Advantages and Benefits:**

Highly effective due to proven formula with high percentages of zinc and aluminium. Excellently suited for sole, decorative corrosion protection. Combines outstanding zinc protection with decorative aluminium gloss. Can be welded through well. Economical due to low consumption and self-cleaning spray valve (no overhead "spraying clear" necessary, and therefore no solvent and propellant gas losses).

## Application:

For best results clean the surfaces, first mechanically and then with OKS 2610/OKS 2611 Universal Cleaner. The surfaces have to be metallic blank and dry. Shake well before use. Spray a thin layer evenly from 20-30 cm distance onto the prepared surface (cross-wise or circularly). Avoid local excess. Drying and curing conditions acc. to the following technical data. For thicker layers repeat the procedure. It is not possible to prime on OKS 2511. Do not use below +10°C and humidity > 80%. For additional questions please contact our Technical Department.

#### **Additional Information:**

Packaging (Article number): - 500 ml Spray (02521005)

Version: E-05.1/05

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitratily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimburesement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. @ = Registered Trademark



## **Technical Data**

	Norm	Conditions	Unit	Value
Solid Lubricants				
Туре				Aluminium, Zinc
Binder				
Туре				Synthetic resin
Solvent				
Туре				Solvent mixture
Film Layer				
Optimal layer thickness	DIN 50 981/50 984	DIN 50 982-2	μm	30 - 40
Application temperature			°C	Room temperature
Drying time		at 20°C	h	0,5
Curing time			h	10 - 12
Curing temperature			°C	20
Surface coverage			m²/Tin	ca. 3
Application Data				
Density	DIN EN ISO 3838	+20°C	g/ml	1,1
Colour				Aluminium coloured
Application Temp	eratures			
Upper application temperature			°C	240
Corrosion Protection Tests				
Salt spray test	DIN 50 021	80 - 100 µm	h	240

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitratily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimburesement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark