

Scapa 5589

PE Double Sided Foam Tape - Black, High Performance Acrylic, 0.8mm

DESCRIPTION

Scapa 5589 is a strong, high performance double-sided foam bonding tape. The product is black. The Polyethylene foam is predominantly closed celled. An acrylic pressure sensitive adhesive is coated on both sides, and the product has a white, Polycoat paper release liner. The material can be supplied with a film liner facilitating automated application.

APPLICATIONS

- Lens edging pads.
- Automotive mirror mounting.
- Automotive emblem mounting.

PRODUCT BENEFITS

- Pre-determined dimensional sealant reduces waste / clean to use.
- No known hazards associated with this product.
- Suitable for indoor and outdoor environments.
- Resistance to abrasion, corrosion and moisture.
- Very good ultraviolet {UV} light resistance.
- Paper release liner, reducing dimensional change during application.
- Good resistance to dilute acids and alkalis.
- Coated on both sides with a high quality pressure sensitive acrylic adhesive.
- Minimum 20% compression required to effect a water seal.
- Shelf life of 1 year from date of dispatch.
- Application temperature: +10°C to +40°C.
- Service temperature: -40°C to +120°C.
- Maximum recommended weight loading of 15 g/cm².

Accreditation:

Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free)

Approved to FIAT specification 9.55368.

Approved by General Motors to GMW 15201 Type III specification for exterior trims.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
10 Minute 180° Peel Adhesion	20	N/25mm	Scapa F9
150 Hour Static shear @ 70 deg C	0.2	Kg/cm ²	Scapa F21
500 hour Static Shear (Stainless Steel)	0.16	Kg/cm ²	Scapa F7
Dynamic Shear	60	N/cm ²	Scapa F11
Elongation at Break	300	%	Scapa F17
T Block (Dynamic tensile) Adhesion (72 hour)	90	N/cm ²	Scapa F11
Tensile Strength	200	N/cm ²	Scapa F17

STANDARD PRESENTATIONS

- Core: 76 mm plastic
- Formats: Logs, rolls, spools
- Thickness: 0.8 mm

Note:

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the shelf life of the tape is 12 months from the date of dispatch.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Customers are recommended to make their own assessment of our products under their own conditions, for their own requirements.